

UPS5000-E

(200-800 kVA)

Introduction

UPS5000-E-(200-800kVA) is an advanced modular UPS based on Huawei's extensive experience in digital technology and power electronics. Benefiting from high performance DSP and high speed communication technology, the UPS5000-E system achieves leading expandability and availability. Its high efficiency, high availability match the requirements of cloud data center perfectly.

Scenarios

- Data centers in headquarter or disaster recovery data centers
- Internet data centers
- Large cloud computing data centers

Features

Reliable

- 138-485Vac ultra-wide input voltage range, suitable for the worst power grid
- Redundant design for modules, elimination of the single point of failure
- iPower pre-warnings for key components in case of power supply interruption

Efficient

- High efficiency up to 95%-96% at most frequently-used load rate
- Intelligent hibernation technology ensures efficient UPS operation
- Single UPS capacity up to 800kVA, 50% footprint saving, more IT rack space

Simple

- Hot swappable power module, bypass module and control module, simple maintenance and expansion in 5 minutes
- iPower real time monitoring system for UPS, PDU and batteries, elimination of manual routing inspection



Power module : 50kVA/3U



UPS5000-E-200/300kVA



UPS5000-E-400/500kVA



UPS5000-E-600kVA



UPS5000-E-800kVA

Specifications

Model		UPS5000-E-200K	UPS5000-E-300K	UPS5000-E-400K	UPS5000-E-500K	UPS5000-E-600K	UPS5000-E-800K
Rated Capacity (kVA/kW)		50-200	50-300	50-400	50-500	50-600	50-800
Number of Power Modules		1-4	1-6	1-8	1-10	1-12	1-16
Mains Input	Input Wiring	3Ph+N+PE					
	Rated Voltage	380/400/415Vac					
	Voltage Range	138-485Vac (305-485Vac for 100% load; 138-305Vac for 40%-100% load)					
	Frequency Range	40-70Hz					
	Total Harmonic Distortion	THDi<3% for 100% linear load					
Bypass Input	Input Power Factor	0.99					
	Rated Voltage	380/400/415Vac					
Battery	Input Frequency	50/60 ± 6Hz					
	Rated Voltage	360-528Vdc (The number of batteries can be selected from 30 to 44; 40 batteries in default) 512Vdc (Li-ion battery: Huawei SmartLi)					
Output	Output Wiring	3Ph+N+PE					
	Voltage	380/400/415Vac ± 1%					
	Frequency	Tracking the bypass input (Normal mode); 50/60Hz ± 0.05% (Battery mode)					
	Waveform	Sine wave (THDv<1% for linear load)					
System	Overload Capacity	Inverter: 100%<load≤110% for 60 mins, then transfer to bypass mode; 110%<load≤125% for 10 mins, then transfer to bypass mode; 125%<load≤150% for 1 min, then transfer to bypass mode; load>150% for 200ms, then transfer to bypass mode;					
	Output Power Factor	1					
Environment	Efficiency	Up to 96%					
	Expandability	4					
	Operating Temperature	0-40°C					
Others	Storage Temperature	-40 to 70°C					
	Relative Humidity	0%-95% (No condensing)					
	Operating Altitude	0-2000m. Above 2000m, derating rate based on EN/IEC 62040-3					
Others	H*W*D (mm)	2000*600*850		2000*1200*850		2000*1400*850	2000*2400*850
	Weight (kg)	285~390	275~450	465~710	515~830	705~1090	1075~1540
	Certifications	CE, CB, RoHS, REACH, WEEE, etc.					
	Communications	Dry contacts, RS485, SNMP					

Remark: For important systems that are related to important economic interests or public security, such as civil aviation management center, financial clearing center, and trading center, the T3 or T4 power supply level specified in TI942 must be used. That is, two UPSs form dual-bus power supply or the UPS and mains form dual-bus power supply.